Uniform Mitigation Verification Inspection Form

	uns form and any do	cumentation pro	vided with the insurance	poncy		
Inspection Date: Dec 16, 2020						
Owner Information						
Owner Name: WIGGINS LAKES CON	Contact Person:					
Address: 790 WIGGINS LAKE DR. NAPLES, FL. 34110			Home Phone:			
City: NAPLES Zip: 34110		Work Phone:				
County: COLLIER			Cell Phone:			
Insurance Company: Policy #:						
Year of Home: 1991	Year of Home: 1991 # of Stories: 2 Email:					
NOTE: Any documentation used in va accompany this form. At least one pho though 7. The insurer may ask additio	tograph must accompan nal questions regarding	y this form to valid the mitigated featu	date each attribute marked are(s) verified on this form.	in questions 3		
1. Building Code : Was the structure but the HVHZ (Miami-Dade or Broward or	counties), South Florida E	Building Code (SFB)	C-94)?			
A. Built in compliance with the F a date after 3/1/2002: Building Pe	rmit Application Date (MN	//////	<u> </u>			
	B. For the HVHZ Only: Built in compliance with the SFBC-94: Year Built For homes built in 1994, 1995, and 1996 provide a permit application with a date after 9/1/1994: Building Permit Application Date (MM/DD/YYYY)///					
C. Unknown or does not meet the	requirements of Answer	"A" or "B"				
2. Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.						
Per 2.1 Roof Covering Type:	mit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance		
1. Asphalt/Fiberglass Shingle	1 ₇ 24 ₇ 20		2020			
2. Concrete/Clay Tile	/ /					
3. Metal	//	_		Ħ		
4. Built Up				H		
5. Membrane				H		
				H		
6. Other						
A. All roof coverings listed above installation OR have a roofing per						
B. All roof coverings have a Miar roofing permit application after 9.						
C. One or more roof coverings do not meet the requirements of Answer "A" or "B".						
D. No roof coverings meet the red	uirements of Answer "A	" or "B".				
3. Roof Deck Attachment: What is the	weakest form of roof dec	k attachment?				
A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.						
B. Plywood/OSB roof sheathing 24"inches o.c.) by 8d common na other deck fastening system or true a maximum of 12 inches in the field.	ils spaced a maximum of ss/rafter spacing that is sl eld or has a mean uplift r	12" inches in the fie nown to have an equesistance of at least	eldOR- Any system of scre livalent or greater resistance 103 psf.	ws, nails, adhesives, than 8d nails spaced		
C. Plywood/OSB roof sheathing 24"inches o.c.) by 8d common na decking with a minimum of 2 nai Inspectors Initials KSL Property Add	ils spaced a maximum of s per board (or 1 nail per	6" inches in the fiel board if each board	dOR- Dimensional lumber is equal to or less than 6 inc	Tongue & Groove		
rroperty Add	ress 100 WIGGING LA	INC DIX. IVAFLE	J, I L. UT I IU			
*This vanification form is valid for un t	o five (5) vecus nuovides	l na matavial abana	ros hava baan mada ta tha s	two stares on		

This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

			of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent istance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least
		D. Reinforce	d Concrete Roof Deck.
	Ħ	E. Other:	
	П	F. Unknown	or unidentified.
		G. No attic a	ccess.
4.			achment: What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks within e or outside corner of the roof in determination of WEAKEST type)
		A. Toe Nails	
			Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
			Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
	Min	imal condition	ons to qualify for categories B, C, or D. All visible metal connectors are:
		\checkmark	Secured to truss/rafter with a minimum of three (3) nails, and
		✓	Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
	П	B. Clips	
			Metal connectors that do not wrap over the top of the truss/rafter, or
			Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
	√	C. Single Wi	Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
	П	D. Double V	** •
			Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
			Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
		E. StructuralF. Other:	Anchor bolts structurally connected or reinforced concrete roof.
	H		or unidentified
	Ħ	H. No attic a	
5.			What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
	П	A. Hip Roof	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter.
		B. Flat Roof	
	\checkmark	C. Other Roo	less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft of Any roof that does not qualify as either (A) or (B) above.
6.	Sec.	A. SWR (als sheathing dwelling B. No SWR.	r Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) o called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the from water intrusion in the event of roof covering loss. or undetermined.
In	spect	tors Initials <u>K</u>	SSL_Property Address 790 WIGGINS LAKE DR. NAPLES, FL. 34110
*T	This v	erification fo	orm is valid for up to five (5) years provided no material changes have been made to the structure or

inaccuracies found on the form.

-	ening Protection Level Chart			Glazed C	penings			·Glazed enings
open form	an "X" in each row to identify all forms of protection in use for each ing type. Check only one answer below (A thru X), based on the weakest of protection (lowest row) for any of the Glazed openings and indicate reakest form of protection (lowest row) for Non-Glazed openings.	or E	dows Entry oors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure		1		1		П	√
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)							
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)							
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007							
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						\overline{V}	
N	Opening Protection products that appear to be A or B but are not verified					Ш		
	Other protective coverings that cannot be identified as A, B, or C							
Х	No Windborne Debris Protection	,	✓					
	Southern Standards Technical Document (SSTD) 12 For Skylights Only: ASTM E 1886 and ASTM E 1996 For Garage Doors Only: ANSI/DASMA 115 A.1 All Non-Glazed openings classified as A in the table above, or no Non-G A.2 One or More Non-Glazed openings classified as Level D in the table above X in the table above A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table opening Protection- Cyclic Pressure and 4 to 8-lb	ve, an n the t Lar	nd no table ge N	Non-Glaze above Aissile (2)	-4.5 lb fo	or skylig	ghts	All Glaze
iı	pty)ings are protected, at a minimum, with impact resistant coverings of the product approval system of the State of Florida or Miami-Dade C or "Cyclic Pressure and Large Missile Impact" (Level B in the table ab	ounty	y and				•	
	ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile – 4.5 lb.) SSTD 12 (Large Missile – 4 lb. to 8 lb.)							
	For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large	Miss	ile = '	2 to 4.5 lb)			
Г	B.1 All Non-Glazed openings classified as A or B in the table above, or no N							
	B.2 One or More Non-Glazed openings classified as Level D in the table about in the table above					classified	d as Leve	l C, N, or X
Г	B.3 One or More Non-Glazed openings is classified as Level C, N, or X in th	e table	e abo	ve				
	Exterior Opening Protection- Wood Structural Panels meeting ywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 20						are co	vered with
_	C.1 All Non-Glazed openings classified as A, B, or C in the table above, or n	•						
	C.2 One or More Non-Glazed openings classified as Level D in the table aborthe table above			_	-	classified	d as Leve	l N or X in
	C.3 One or More Non-Glazed openings is classified as Level N or X in the ta	hle ah	20110					
L	2.3 One of Word Won-Glazed openings is classified as Deverty of A in the ta	oic ao	JOVE					

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter sprotective coverings not meeting the requirements of An with no documentation of compliance (Level N in the tax)	nswer "A", "B", or C" or systems tha				
N.1 All Non-Glazed openings classified as Level A, B, C, c N.2 One or More Non-Glazed openings classified as Level table above					
N.3 One or More Non-Glazed openings is classified as Leve	el X in the table above				
X. None or Some Glazed Openings One or more Glazed	ed openings classified and Level X in	the table above.			
MITIGATION INSPECTIONS MUST E Section 627.711(2), Florida Statutes, prov	ides a listing of individuals who may				
Qualified Inspector Name: KENNETH SCOTT LAWRENCE	RESIDENTIAL CONTRACTOR	License or Certificate #: CRC1329147			
Inspection Company: VERSIFI HOMES INC.	Phone:	239-333-7723			
Qualified Inspector – I hold an active license as a	: (check one)				
Home inspector licensed under Section 468.8314, Florida Statutes who has completed the statutory number of hours of hurricane mitigation training approved by the Construction Industry Licensing Board and completion of a proficiency exam. Building code inspector certified under Section 468.607, Florida Statutes. General, building or residential contractor licensed under Section 489.111, Florida Statutes. Professional engineer licensed under Section 471.015, Florida Statutes. Professional architect licensed under Section 481.213, Florida Statutes. Any other individual or entity recognized by the insurer as possessing the necessary qualifications to properly complete a uniform mitigation verification form pursuant to Section 627.711(2), Florida Statutes.					
Individuals other than licensed contractors licensed under Section 489.111, Florida Statutes, or professional engineer licensed under Section 471.015, Florida Statues, must inspect the structures personally and not through employees or other persons. Licensees under s.471.015 or s.489.111 may authorize a direct employee who possesses the requisite skill, knowledge, and experience to conduct a mitigation verification inspection. I, Kenneth Scott Lawrence am a qualified inspector and I personally performed the inspection or (licensed (print name) contractors and professional engineers only) I had my employee (N/A) perform the inspection (print name of inspector) and I agree to be responsible for his/her work. Qualified Inspector Signature: Date: Dec 16, 2020 An individual or entity who knowingly or through gross negligence provides a false or fraudulent mitigation verification form is subject to investigation by the Florida Division of Insurance Fraud and may be subject to administrative action by the appropriate licensing agency or to criminal prosecution. (Section 627.711(4)-(7), Florida Statutes) The Qualified Inspector who certifies this form shall be directly liable for the misconduct of employees as if the authorized mitigation inspector personally performed the inspection.					
Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification	n was provided to me or my Authoriz				
Signature:	Date: Dec 16, 2020	<u></u>			
An individual or artity who knowingly provides or atters	false on fraudulant mitigation vari	fination form with the intent to			
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to w of the first degree. (Section 627.711(7), Florida Statutes)					
The definitions on this form are for inspection purposes on as offering protection from hurricanes.	ly and cannot be used to certify an	y product or construction feature			
Inspectors Initials KSL Property Address 790 WIGGINS LAKE DR. NAPLES, FL. 34110					
*This verification form is valid for up to five (5) years provinaccuracies found on the form.	ided no material changes have bee	n made to the structure or			

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 4 of 4



Image Field

FE-1 WINDOWS WITH NO PROTECTION



Image Field

FE-3 UNGLAZED DOOR IS WIND RATED



Image Field

RE-1 WINDOWS WITH NO PROTECTION



Image Field

FE-2 ADDRESS VALIDATION



Image Field

FE-4 WINDOWS WITH NO PROTECTION



lmage Field

RE-2 WINDOW WITH NO PROTECTION



Image Field

BE-1 WINDOWS WITH NO PROTECTION



Image Field

BE-3 WINDOWS WITH NO PROTECTION



Image Field

LE-2 WINDOW WITH NO PROTECTION



Image Field

BE-2 GLAZED DOORS WITH NO PROTECTION



Image Field

LE-1 WINDOWS WITH NO PROTECTION



Image Field

A-1 FRONT STRAP WITH 2 NAILS



Image Field

A-2 BACK OF STRAP WITH 1 NAIL



A-3 FRONT STRAP WITH 3 NAILS



Image Field

A-4 BACK OF STRAP WITH 2 NAILS



Image Field

A-5 8D NAIL ROOF DECK ATTACHMENT



Image Field

A-6 1/2" ROOF DECKING



Image Field

A-7 6" SPACING OF FASTENERS IN FIELD OF DECKING



Image Field

A-8 SWR PHOTO IN ATTIC

Image Field

Image Field Image Field

Image Field

Image Field

New Page

GMD Public Portal

Permit Application Status

In order to view fees or schedule inspections, you need to be signed in.

_	Summary	
	,	
	Application Number:	PRBD20200416359
	Application Type:	Building
	Application Status:	Inspections Completed
	Property Owner's Full Name:	REFERENCE ONLY WIGGINS LAKES CONDOMINIUM
	Category of Work:	Alteration
	Occupancy Code:	Utility, Miscellaneous - Residential
	Description of Work:	Shingle Re-Roof 790 Wiggins Lake DR, Unit: BLDG 16, Naples
	Application Date:	04/24/2020
	Issued Date:	06/18/2020
	Expiration Date:	01/12/2021
	1-2 Family or Comm:	Commercial
	Locations	
	Contacts	
_	Contacts	
_	Permits (Click to See Reviews)	
_	Deposits & Bonds	
_	Inspections	
	Conditions	
_	Conditions	
_	Documents & Images	

1 of 1 12/15/2020, 7:42 PM